



# AC Pro Spec Sheet | UAP-AC-Pro

Ceiling-mounted WiFi 5 AP with 6 spatial streams designed for large offices.

- WiFi 5
- 6 spatial streams
- 140 m<sup>2</sup> (1,500 ft<sup>2</sup>) coverage
- 250+ connected devices
- Powered using PoE
- GbE uplink

## Mechanical

<b>Dimensions</b>	Ø196.7 x 35 mm
<b>Weight</b>	Without mount: 350 g
	With mount: 450 g

---

## Hardware

<b>Networking interface</b>	(2) GbE RJ45 port
<b>Management interface</b>	Ethernet
<b>Power method</b>	PoE
	Passive PoE, 48V
<b>Power supply</b>	UniFi PoE switch
	48V, 0.5A PoE adapter (Included)
<b>Supported voltage range</b>	44—57V DC
<b>Max. power consumption</b>	9W
<b>Max. TX power</b>	
<b>2.4 GHz</b>	22 dBm
<b>5 GHz</b>	22 dBm
<b>6 GHz</b>	-
<b>MIMO</b>	
<b>2.4 GHz</b>	3 x 3
<b>5 GHz</b>	3 x 3
<b>6 GHz</b>	-
<b>Max. data rate</b>	
<b>2.4 GHz</b>	450 Mbps
<b>5 GHz</b>	1.3 Gbps

<b>6 GHz</b>	-
<b>Antenna gain</b>	
<b>2.4 GHz</b>	3 dBi
<b>5 GHz</b>	3 dBi
<b>6 GHz</b>	-
<b>Button</b>	Factory reset
<b>Mounting</b>	Wall, ceiling (Included)
<b>Ambient operating temperature</b>	-10 to 70° C
<b>Ambient operating humidity</b>	5 to 95% noncondensing
<b>Certifications</b>	CE, FCC, IC
<hr/>	
<b>Software</b>	
<b>WiFi standards</b>	802.11a/b/g/n/ac
<b>Wireless security</b>	WEP, WPA-PSK, WPA-Enterprise (WPA/WPA2, TKIP/AES)
<b>BSSID</b>	4 per radio
<b>VLAN</b>	802.1Q
<b>Advanced QoS</b>	Per-user rate limiting
<b>Guest traffic isolation</b>	Supported
<b>Power Save</b>	Supported
<b>WMM</b>	Voice, video, best effort, and background
<b>Concurrent clients</b>	250+
<hr/>	
<b>Supported Data Rates</b>	
<b>802.11a</b>	6, 9, 12, 18, 24, 36, 48, 54 Mbps
<b>802.11b</b>	1, 2, 5.5, 11 Mbps
<b>802.11g</b>	6, 9, 12, 18, 24, 36, 48, 54 Mbps
<b>802.11n</b>	6.5 Mbps to 450 Mbps
<b>802.11ac</b>	6.5 Mbps to 1.3 Gbps